

Urban Land Use Planning using Answer Set Programming

- Preliminary Report -

Jennifer Muñoz¹ and Flavio Everardo²

¹ Universidad Popular Autónoma del Estado de Puebla
and Instituto de Ciencias de la Benemérita Universidad Autónoma de Puebla

jenniferjocelin@hotmail.com

² Universidad de las Américas Puebla

flavioeverardo@gmail.com

Puebla, Mexico

Abstract. The urban planning is required to direct the cities development based on the sustainable use of its territory. On the other hand, Answer Set Programming (ASP) is a logic programming paradigm with the ability of non-monotonic reasoning, which has contributed to solving complex problems in a short period of time, providing a considerable number of possible outcomes to the same problem. The treatment of sustainable urban planning by using a declarative approach like ASP has not been proposed so far. This article aims to demonstrate a modelling exercise using basic knowledge about a mix of urban land usage. Also, to show alternatives for a better functional integration of green and habitational areas, as well as a discussion of further research using this approach.

Keywords: Urban Planning, Urban Land Usage, Answer Set Programming, Knowledge Representation and Reasoning

1 Introduction

The need to think about an ordered cities growth and their development, are not new topics. The proposal on strategic measurements to improve the conditions of cities, is one of the issues considered in the Agenda 21, to promote the construction of an international sustainable model for the twenty-first century [13].

Derived from the above, with support from the United Nations Environment Programme (UNEP), different countries worldwide have joined forces in order to adapt environmental policies into their development processes with a sustainable approach. The Institute of Hygiene, Epidemiology and Microbiology of the Ministry of Public Health of Cuba in coordination with the World Health Organization (WHO) and UNEP through the Latin American and the Caribbean Regional Office, have proposed a classification of six universal principles for planning a sustainable urban ecosystem [19]:

1. Ensure proper water supply.
2. Keep protected vegetation.
3. Preserve soil quality.
4. Ensuring sustainable conditions for wildlife.
5. Keeping potential of regional food production.
6. Create a human scale urban environment.

Taking into consideration the principles 2,3 and 6, this article proposes forming a basic knowledge that serves an intelligent system in resolving a complex combinatorial problem such as urban land use planning. Initially this article mentions works that use Knowledge Representation (KR) as a support in the field of organization of urban territories, then the land use term is defined as part of sustainable urban planning and an introduction to ASP is provided. Consecutively both issues are linked to generate a proposal where ASP contributes to the definition of urban land use. This paper concludes with a discussion of the preliminary results and future work.

2 Backgrounds

Land use and urban planning in general have been areas of interest to the scientific community. Reason why, they have developed works that employ technology as a way to propose alternatives for cities improvement. For purposes of this paper, the works mentioned below have used some method of KR.

One of the first works is the URBYS system, defined as an expert system for urban areas analysis through KR for decision-making [16]. There are studies that address the selection of industrial zones [17] under a system called MATISSE which, by decision tables represents knowledge as a set of rules and their respective actions. Likewise decision tables have also been used to introduce functional classification theory to land use planning [18].

Changing the subject, ontologies is another used and proven approach in works like OSMoSys [12] which seeks to harness the potential of Web applications as interactive tool gathering information from urban areas as well as information generated by humans through smart devices and social platforms.

It should be noted that these examples have used different approaches of AI to resolve urban problematics. Nevertheless, so far none has taken advantage of the benefits of ASP to solve these problems and that is why the strategy proposed in this article is unique in its class.

3 Land Use within Sustainable Urban Planning

A standard definition of land use is the employment that humans make the earth's surface, covering the management and modification of the natural environment to make it a built environment³. Examples are human settlements that

³ https://en.wikipedia.org/wiki/Land_use

involve industrial parks, shopping centers, roads, green and residential areas, among others.

Within the universal principles for sustainable urban ecosystem planning previously mentioned, three of them are directly linked to land use planning purposes considering the functional integration between green and residential use areas [8].

This work considers the functional integration of green and residential areas as part of land use planning in a city. Reasons why the principles, protected vegetation, soil quality and human scale urban environment are interrelated. The fact that exists areas with trees, keep soil and air quality and this kind of conditions are attractive for living. These three principles handle certain rules, restrictions, conventions or preferences that allow forming a knowledge base for modeling desirable behavior in order to adapt to conventional urban spaces.

4 Answer Set Programming

Several researchers have proposed the use of ASP as a solution to the paradigm of Knowledge Representation and Reasoning (KRR) [2] [7] [9] [10], also since its inception, ASP has been considered as the most suitable and effective computational processing mode for non-monotonic reasoning and KR [2] [3] [11]. This perspective has promoted the creation of high performance and efficiency Answer Set Solvers.

ASP has been tested successfully in areas, which involve problems of combinatorial search using a considerable amount of information to process [7]. It is noteworthy that at the University of Potsdam has developed software as Clasp, Gringo [5], Clingo [6], among others⁴, which have been recognized worldwide for its capacity and performance applied in ASP [1] [4].

Additionally, ASP is based on a simple yet expressive rule language that allows users to easily model problems in a compact form. The solutions to such problem are known as answer sets or stable models [15].

4.1 Problem Representation in Logic Form

To properly represent a problem it is necessary to segment it into three logical components: Facts and Constraints, Preferences and Real Scenarios or Input:

- Facts and Constraints: are those foundations that we can get from a specific problem whether they are not going to change or are prohibited. In other words are the guidelines and parameters involving sustainable urban planning.
- Preferences: Establish rules and restrictions about situations preferable over others [14].

⁴ More information about the Potsdam Answer Set Solving Collection software: <http://potassco.sourceforge.net>

Modeling rules, constraints and preferences give us the parameters of what is desirable, undesirable and preferably having and not having to solve a problem based on the input. This information will be extracted from literature and real sustainable cases (RSC) to become KB (Fig1).




Fig. 1. Information extraction to create KB

- The Real Scenario or Inputs: refers to the current situation once modeled the problem. This needs to include a well-detailed description or specific characteristics of a determined urban center. This set will call R (Fig2).




Fig. 2. Real or fiction case extraction to create R

If R changes, the result will be different even if KB does not change. The benefits of ASP allow us depending on the complexity of the problem, is possible to have a wide range of perspectives for decision-making from the same R.

5 Land Use Representation in ASP

Once represented a complex problem as specified in the preceding paragraphs, it is necessary to translate this information into logical language for ASP. Taking as example urban land usage, there may be more than 3 or 4 ways to grow a city or use lands in a proper way.

Positions		
1	2	3
House	House	Green Area
House	Green Area	House
4	5	6

Fig. 3. Example of houses and green areas distribution by KB definition

The Figure above (Fig3) shows an example of an area which it has been demonstrated to be appropriate to build residential houses and green areas, but the field should contain one-third of green areas at all times. In other words if we have an area that can store 6 buildings, 2 of these must be green areas, the other 4 must be houses.

To represent KB we can define two rules such as: 1. In each position is possible to build whether a house or a green area. 2. Desirable number of green areas is equal to the total space divided by 3.

Listing 1.1. Basic Land Use Example in ASP

```

1 1{houseInPosition(P),greenAreaInPosition(P)}1:-position(P).
2 1 {houseType(C,P) : house(C)} 1 :- houseInPosition(P).
3
4 housesNumber(N)      :- N = #count {houseInPosition(C)}.
5 greenAreasNumber(N)  :- N = #count {greenAreaInPosition(C)}.
6
7 desiredNumberOfGreenAreas(A/3) :- area(A).
8 :-greenAreasNumber(N),desiredNumberOfGreenAreas(NAV),N!=NAV.
9
10 built(house,TC,P)    :- houseType(TC,P).
11 built(greenArea,P)  :- greenAreaInPosition(P).

```

The Basic Land Use Example code above shows the set of rules and restrictions that arises for KB where lines 1 and 2 talk about the rule 1. Lines 4 and 5 carry the counting houses and green areas. Line 7 calculates the total of green areas to have by dividing the total space by 3 and line 8 restricts that the number of green areas were different than the calculated. Finally, lines 10 and 11 indicate where the houses and green areas will be built. On the other hand it is

necessary to define the current scenario or R1 defining a first example indicating that the area is of size 6 and there is only one kind of house to be built.

Listing 1.2. Basic Land Use Example for R1

```

1 area(6).                %% Area with 6 slots for construction
2 position(1..A) :- area(A). %% Therefore there are 6 positions
3 house(1..1).           %% Exist 1 type of house
4
5 %% Constraint that in the 5th position a house must be built
6 %% This can be a bad quality land
7 :- built(greenArea,5).
```

If only using the first three lines, we can see that there is a total of 15 solutions combining in the 6 spaces, the number of houses and green areas respecting the corresponding number of green areas. Adding the constraint that the area number 5 is not suitable for a green area construction, so a house must be built. This may satisfy certain qualities of the land mentioned in the previous section. Running this example will deliver a total of 10 solutions. This amount of results could simplify decision-making, but it is possible that in another scenario R2, there are three different models of houses to be built. The complexity of this issue has been raised for a total of 1,215 viable results. It is worth to mention that if we add the same constraint listed above, the number of results will decrease to 810.

Listing 1.3. Basic Land Use Example for R2

```

1 area(6).                %% Area with 6 slots for construction
2 position(1..A) :- area(A). %% Therefore there are 6 positions
3 house(1..3).           %% Exists 3 types of houses
```

Finally, if later we found a real scenario like R3 expressing a land where fits 9 buildings instead of 6, and applying the same KB, the total results exponentially increase to 61,236. Again, by adding the mentioned constraint we can limit the result to 40,824.

Listing 1.4. Basic Land Use Example for R2

```

1 area(9).                %% Area with 9 slots for construction
2 position(1..A) :- area(A). %% Therefore there are 9 positions
3 house(1..3).           %% Exists 3 types of houses
```

In summary, KB has not changed over time but R has exemplified three different cases and the results show an exponential growth leading to an extensive analysis before a decision can be made. The more complex the problem, the more results we can get. It is worth noting that the greater the details modeled in R including constraints, more specific results we can get, limiting an exponential growth and making easier the analysis of the results and decision-making.

6 Discussion

In this paper is presented a new and innovative approach to begin to contribute to the understanding of the urban structure and planning with the help of ASP. Also it is demonstrated that a declarative programming perspective fits properly in the urban problems modeling.

It is worth mentioning that the set of characteristics of an urban society is manifested in its territorial structure, therefore, each city will have a different soil use structure [8]. This article does not include a detailed description of the spatial structure of an urban center in particular; reason why it is planned for future research, enrich KB so it is enough to adapt to different escenarios. In order to find the best plan for land use structuring or restructuring, considering the needs of functional integration for a specific urban ecosystem, and also, respecting the methodology and problem-solving strategy presented in this article. Hence is considered possible to explore and venture later in the 6 universal principles for sustainable urban planning.

Finally, once advanced the following works where both KB and R are in a higher level of maturity, we will seek to test four hypotheses, which are:

- Review a real scenario R to determine whether or not this particular zone makes a proper use of lands.
- Recommendations or modifications for R with the purpose of finding alternatives to fulfill a proper land use management.
- Projections of how R can be developed in short, medium and long term.
- Forecasts that show how R could grow if certain changes or adjustments on prior knowledge are not made.

References

1. Mario Alviano, Francesco Calimeri, Günther Charwat, Minh Dao-Tran, Carmine Dodaro, Giovambattista Ianni, Thomas Krennwallner, Martin Kronegger, Johannes Oetsch, Andreas Pfandler, et al. The fourth answer set programming competition: Preliminary report. In *Logic Programming and Nonmonotonic Reasoning*, pages 42–53. Springer, 2013.
2. Christian Anger, Kathrin Konczak, Thomas Linke, and Torsten Schaub. A glimpse of answer set programming. *KI*, 19(1):12, 2005.
3. Chitta Baral. *Knowledge representation, reasoning and declarative problem solving*. Cambridge university press, 2003.
4. Francesco Calimeri, Giovambattista Ianni, and Francesco Ricca. The third open answer set programming competition. *Theory and Practice of Logic Programming*, 14(01):117–135, 2014.
5. M. Gebser, T. Schaub, and S. Thiele. Gringo: A new grounder for answer set programming. *Logic Programming and Nonmonotonic Reasoning*, pages 266–271, 2007.
6. Martin Gebser, Roland Kaminski, Benjamin Kaufmann, and Torsten Schaub. Clingo= asp+ control: Preliminary report. *arXiv preprint arXiv:1405.3694*, 2014.

7. Michael Gelfond and Yulia Kahl. *Knowledge representation, reasoning, and the design of intelligent agents: The answer-set programming approach*. Cambridge University Press, 2014.
8. Ignacio Kunz. *Usos de suelo y territorio: tipos y lógicas de localización en la ciudad de México*. Plaza y Valdés, 2003.
9. Nicola Leone, Gerald Pfeifer, Wolfgang Faber, Thomas Eiter, Georg Gottlob, Christoph Koch, Cristinel Mateis, Simona Perri, and Francesco Scarcello. The dlv system for knowledge representation and reasoning. 2002.
10. V. Lifschitz. What is answer set programming. In *Proc. of AAAI*, pages 1594–1597, 2008.
11. Ilkka Niemelä. Logic programs with stable model semantics as a constraint programming paradigm. *Annals of Mathematics and Artificial Intelligence*, 25(3-4):241–273, 1999.
12. Achilleas Psyllidis. Ontology-based data integration from heterogeneous urban systems: A knowledge representation framework for smart cities. In *CUPUM 2014: Proceedings of the 14th International Conference on Computers in Urban Planning and Urban Management, Cambridge, USA, 7-10 July 2015*. MIT, 2015.
13. Nicholas A Robinson, LE Astorga, T Oksanen, EJ Trigo, O Pastora, P Pastor, S de Izaguirre, AC Padgett, R Arita Arita, H Palma, et al. *Agenda 21: earth's action plan*. Number GTZ-798. IUCN, Gland (Suiza)., 1993.
14. Torsten Schaub. Preferences in answer set programming.
15. Patrik Simons, Ilkka Niemelä, and Timo Soinen. Extending and implementing the stable model semantics. *Artificial Intelligence*, 138(1):181–234, 2002.
16. Emile Tanic. Urban planning and artificial intelligence: the urbys system. *Computers, Environment and Urban Systems*, 10(3):135–146, 1986.
17. Frank Witlox. Matisse: a relational expert system for industrial site selection. *Expert systems with applications*, 24(1):133–144, 2003.
18. Frank Witlox, Marc Antrop, Peter Bogaert, Philippe De Maeyer, Ben Derudder, Tijs Neutens, Veronique Van Acker, and Nico Van de Weghe. Introducing functional classification theory to land use planning by means of decision tables. *Decision Support Systems*, 46(4):875–881, 2009.
19. Annalee Yassi, Tord Kjellstrom, Theo deKok, and Teco Guidotti. *Salud ambiental básica*. Oficina Regional de Cultura para América Latina y el Caribe, 2002.